

# Litchi

L1600/L1601/L1602

Form Meets Function in Metal



## Rich Functions, Versatile Scenarios

15.6" main screen, coupled with optional 15.6"/10.1" secondary screen, rich peripherals and comm options, enables versatile use cases with different choices.



# Specifications

Model Name: : L1600/L1601/L1602



## Operating System

Android™12, GMS Certified  
with Supporting UNIPHIZ UI



## Processor

Quad-Core  
Cortex® - A55 2.0GHz



## Memory

LPDDR4X 4GB + eMMC 64GB  
External:  
microSD Card slot(Up to 128GB)



## Displays

Main Display:  
15.6" 1920 × 1080 px IPS FHD Touch Screen  
Secondary Display:  
L1600: N/A  
L1601: 10.1" 1280 × 800 px IPS Screen, optional touch  
L1602: 15.6" 1920 × 1080 px IPS Screen, optional touch



## Ports

1 \* Type-A 3.0 | 3 \* Type-A | 1 \* Type-C 3.0  
1 \* LAN (1000M) | 1 \* DK (RJ11, 24V / 12V)  
1 \* RS232(RJ45) | DC IN | Audio Jack  
6-Pin Pogo Pin (opt)



## Cameras

Main Screen Camera (opt):  
5MP Auto Focus  
Secondary Screen Camera (opt):  
5MP Auto Focus



## Comms Configurations

Wi-Fi® 2.4GHz / 5GHz  
Bluetooth® 5.0



## Card Readers (opt)

NFC on the secondary  
screen (Card Reader,  
Card Emulation)



## Audio

Speaker: 3W  
Microphone



## Button

Power Button



## SAM

Optional: 1 \* Mini SAM



## Power

Input: 100-240V AC, 1.0A  
Output: 24V DC, 1.5A



## Power Indicator

White LED



## Physical

364.6×220.0×322.4mm  
1600: 5kg  
1601: 6kg  
1602: 7kg



## Environmental

Operating Temperature: 0°C ~ 50°C (32°F ~ 122°F)  
Storage Temperature: -20°C ~ 60°C (-4°F ~ 140°F)  
Relative Humidity: 10% ~ 93%, non-condensing